



Connection	Type	Diameter	Thickness	PCD	Bolt Hole	No	Weight	Product
Size	of	of Flange	of Flange	of Flange	Diameter	of	Per Flange	Code
'A' mm	Flange	B' ins	C' mm	D' ins	E' ins	Bolts	Kilos	Zinc Plated
15	16/3	95	10	65	14	4	0.6	110C015012
20	16/3	105	10	75	14	4	0.65	110C020012
25	16/3	115	10	85	14	4	0.95	110C025012
32	16/3	140	10	100	18	4	1.3	110C032012
40	16/3	150	10	110	18	4	1.6	110C040012
50	16/3	165	10	125	18	4	1.75	110C050012
65	16/3	185	10	145	18	4	2	110C065012
80	16/3	200	10	160	18	8	2.2	110C080012
100	16/3	220	10	180	18	8	2.45	110C100012
125	16/3	250	12	210	18	8	3.4	110C125012
150	16/3	285	12	240	22	8	3.8	110C150012
200	10/3	340	12	295	22	8	5.3	110C200012
250	10/3	395	15	350	22	12	8.5	110C250015
300	10/3	445	19	400	22	12	12.1	110C300019
350	10/3	505	22	460	22	16	18	110C350022
400	10/3	565	22	515	22	16	21	110C400022
450	10/3	615	25	565	26	20	27	110C450025
500	10/3	670	25	620	26	20	32	110C500025
600	10/3	780	25	725	30	20	39	110C600025
700	10/3	895	30	840	30	24	48	110C700030
800	10/3	1015	35	950	33	24	71.5	110C800035
900	10/3	1115	40	1050	33	28	90	110C900040
1000	10/3	1230	45	1170	36	28	121	110C100045
1200	10/3	1455	50	1380	39	32	179	110C120050
200	16/3	340	12	295	22	12	5.25	113C200012
250	16/3	405	15	355	26	12	8.75	113C250015
300	16/3	460	19	410	26	12	12.5	113C300019
350	16/3	520	22	470	26	16	18.5	113C350022
400	16/3	580	22	525	30	16	21.5	113C400022

110/113 – Mild steel PN10/PN16 Backing Flanges – Zinc plated –
Scotchkote – PPA coated



Connection	Type	Diameter	Thickness	PCD	Bolt Hole	No	Weight	Product
Size	of	of Flange	of Flange	of Flange	Diameter	of	Per Flange	Code
'A' mm	Flange	B' ins	C' mm	D' ins	E' ins	Bolts	Kilos	Zinc Plated
450	16/3	640	25	585	30	20	28	113C450025
500	16/3	715	25	650	33	20	34	113C500025
600	16/3	840	25	770	36	20	42	113C600025
700	16/3	910	35	840	36	24	51.5	113C700030
800	16/3	1025	44	950	39	24	74	113C800035
900	16/3	1125	40	1050	39	28	93	113C900040
1000	16/3	1225	45	1170	42	28	135	113C100045
1200	16/3	1485	50	1390	48	32	198	113C120050