

Rolled Edge Flat Bar is supplied to the following tolerances.

The information is taken from BS EN 10058.

Special Tolerances may be available upon request for production orders.

THICKNESS TOLERANCES

Nominal Thickness (mm)	Tolerance (mm) + or -
Up to & incl. 20	0.5
Over 20 up to & incl. 40	1.0
Over 40 up to & incl. 60	1.5

WIDTH TOLERANCES

Nominal Width (mm)	Tolerance (mm) + or -
10 up to & incl. 40	0.75
Over 40 up to & incl. 80	1.0
Over 80 up to & incl. 100	1.5
Over 100 up to & incl. 120	2.0
Over 120 up to & incl. 150	2.5

STRAIGHTNESS TOLERANCES

Nominal Cross Section (mm ²)	Tolerance (mm)
Below 1000	Below 0.4% of measuring length
1000 and above	Below 0.25% of measuring length

OUT OF SECTION TOLERANCES

Nominal Thickness (mm)	Tolerance (mm)
10 up to & incl. 25	0.5
Over 25 up to & incl. 40	1.0
Over 40 up to & incl. 80	1.5

CONTACT

Address: Unit 8, Petre Court
 Clayton Le Moors
 Accrington
 Lancashire
 BB5 5HY
Tel: +44 (0)1254 775133
Web: <https://www.stainlessmetricstock.com/>

REVISION HISTORY

Datasheet Updated 18 July 2019

DISCLAIMER

This Data is indicative only and as such is not to be relied upon in place of the full specification. In particular, mechanical property requirements vary widely with temper, product and product dimensions. All information is based on our present knowledge and is given in good faith. No liability will be accepted by the Company in respect of any action taken by any third party in reliance thereon.

Please note that the 'Datasheet Update' date shown above is no guarantee of accuracy or whether the datasheet is up to date.

The information provided in this datasheet has been drawn from various recognised sources, including EN Standards, recognised industry references (printed & online) and manufacturers' data. No guarantee is given that the information is from the latest issue of those sources or about the accuracy of those sources.

Material supplied by the Company may vary significantly from this data, but will conform to all relevant and applicable standards.

As the products detailed may be used for a wide variety of purposes and as the Company has no control over their use; the Company specifically excludes all conditions or warranties expressed or implied by statute or otherwise as to dimensions, properties and/or fitness for any particular purpose, whether expressed or implied.

Advice given by the Company to any third party is given for that party's assistance only and without liability on the part of the Company. All transactions are subject to the Company's current Conditions of Sale. The extent of the Company's liabilities to any customer is clearly set out in those Conditions; a copy of which is available on request.