

SMS-109/111 - Mild Steel Table D/E Backing Flanges - Zinc Plated

Connection	Type	Diameter	Thickness	PCD	Bolt Hole	No	Weight	Product
Size	of	of Flange	of Flange	of Flange	Diameter	of	Per Flange	Code
'A' mm	Flange	'B' ins	'C' mm	'D' ins	'E' ins	bolts	Kilos	Zinc Plated
15	D/E	3 3/4	10	2 5/8	9/16	4	0.60	109C015012
20	D/E	4	10	2 7/8	9/16	4	0.65	109C020012
25	D/E	4 1/2	10	3 1/4	9/16	4	0.95	109C025012
32	D/E	4 3/4	10	3 7/16	9/16	4	1.05	109C032012
40	D/E	5 1/4	10	3 7/8	9/16	4	1.30	109C040012
50	D/E	6	10	4 1/2	11/16	4	1.45	109C050012
65	D/E	6 1/2	10	5	11/16	4	1.50	109C065012
80	D/E	7 1/4	10	5 3/4	11/16	4	1.90	109C080012
100	D	8 1/2	12	7	11/16	4	2.50	109C100012
100	E	8 1/2	12	7	11/16	8	2.45	111C100012
125	D/E	10	12	8 1/4	11/16	8	3.40	109C125012
150	D	11	12	9 1/4	11/16	8	3.85	109C150012
150	E	11	12	9 1/4	7/8	8	3.80	111C150012
200	D	13 1/4	12	11 1/2	11/16	8	5.40	109C200012
200	E	13 1/4	12	11 1/2	7/8	8	5.30	109C200012
250	D	16	15	14	7/8	8	8.75	109C250015
250	E	16	15	14	7/8	12	8.50	111C250015
300	D	18	19	16	7/8	12	12.20	109C300019
300	E	18	19	16	1	12	12.10	111C300019
350	D/E	20 3/4	22	18 1/2	1	12	18.50	109C350022
400	D/E	22 3/4	22	20 1/2	1	12	21.50	109C400022
450	D	25 1/4	25	23	1	12	27.50	109C450025
450	E	25 1/4	25	23	1	16	27.25	111C450025
500	D/E	27 3/4	25	25 1/4	1	16	32.50	109C500025
600	D	32 1/2	25	29 3/4	1 1/8	16	41.50	109C600025
600	E	32 1/2	25	29 3/4	1 1/4	16	41.00	111C600025